BENTLEY CROSSING Stage 1 BUILDING SETBACK PLAN

Notes:

- 1. Front, side & rear boundary setbacks are from the Outer Most Projection (OMP) to the relevant boundary.
- 2. For a corner lot which has an average width of 24m or less, no building or structure over 2 metres in height is to be built within a 9 metre truncation at the corner of two road frontages.
- 3. All buildings must be set back a minimum of 1.5 metres to completed sewer mains, or as otherwise approved. Note: Deeper sewer mains may require an increased setback (refer to Council.).
- 4. Where there is conflict between the approved setbacks and drainage, sewer or water infrastructure the infrastructure position prevails together with required setbacks from such infrastructure.
- 5. The two storey parts of a detached dwelling have a minimum set back of 2 metres to the relevant boundary.
- 6. The maximum length of a building built to a side boundary is restricted to 15 metres. That part of the building that is built-to-boundary is to only contain non-habitable rooms. If building is constructed in two sections the infill between the two sections must be joined with a 1.8 metre high masonry fence matching the subject dwelling.
- 7. Where no set backs are provided on the approved plans the Queensland Development Code shall prevail. refer QDC "MP1.1 Design and siting Standard for Single detached Housing on lots less than 450m2" & refer "QDC MP1.2 Design and siting Standard for Single detached Housing on lots 450m2 and over"
- 8. Edge of Driveway to face of Electrical Fuse Pillar to have a minimum clearance of 1.0m.

			Front	Secondary	Garage	Minimum Side and Rear clearances	
		Lot	Street	Street	Street	from that part of Building or structure	
Lot	Area	Frontage	Setback	Setback	Setback	that is	
						4.5m or less in	4.501m to 7.5m in
						height *	height*
	m2	m	m	m	m	m	m
101	740	11.28	6.0		6.0	1.500	2.000
102	555	17.39	6.0		6.0	1.500	2.000
103	525	17.36	6.0		6.0	1.500	2.000
104	540	18.00	6.0		6.0	1.500	2.000
105	600	20.00	6.0		6.0	1.500	2.000
106	657	20.79	6.0		6.0	1.500	2.000
107	808	30.57	6.0	3.0	6.0	1.500	2.000
108	620	20.26	6.0		6.0	1.500	2.000
109	914	33.52	6.0		6.0	1.500	2.000

* unless reduced Setback is permitted as per Note 7

